



- 1. ZRS afdichtingsring
- 2. Ondersteuning drukring
- 3. Axiaal deel
- 4. Draaipunt
- 5. Buitenring
- 6. Cilinderrollen
- 7. Binnenring
- 8. ZRS afdichtingsring

Technische data Combinatielagers -I- profiel

Type	d	T	D	H	h	B	A	S	r	C kN	Co kN	Ca kN	Coa kN	D op bestelling	Voor profiel
400-0055/1 (4.0055/1)	35	48	70,1	40	30,5	23	2,5	22	4	55,5	91,7	17,6	25	70,4/70,7	3018
400-0057 (4.0057)	40	53	77,7	40,7	29	23	3	26	4	58,4	100	28,2	35,8	78,1/78,5	3019
400-0058 (4.0058/2)	45	59	88,4	52	39	30	3,5	26	3	83,8	132,3	27,7	42	88,9	3020
400-0059 (4.0059)	50	67	101,2	46	33	28	3	30	3	91	150	31	49	101,9	2912
400-0060 (4.0060)	55	71	107,7	53	39	31	3	34	5	92,5	157	38	65	108,2/108,5	3100

- C = dynamisch draaggetal
- Co = statisch draaggetal
- Ca = axiaal dynamisch draaggetal

- Coa = axiaal statisch draaggetal
- Lasbare astap uit staal St52 - toelantie -0,05mm