



1. ZRS seal ring
2. Support thrust ring
3. Axial part
4. Pivot

5. Outer ring
6. Cylindrical rollers
7. Inner ring
8. ZRS seal ring

Technical data Fixed combination bearings for -U- profil

Type	d	T	D	H	h	B	A	S	R	C kN	Co kN	Ca kN	Coa kN	D on order	for profile
400-0053 (4.0053)	30	40	52,5	33	27	17	5	15	2	24,8	34,5	9,2	11,7	upon request	S/ EC053
400-0054 (4.0054)	30	42	62	37,5	30,5	20	2,5	20	3	39	65,2	14,4	21	62,5	2890
400-0055 (4.0055)	35	48	70,1	44	36	23	2,5	22	4	55,5	91,7	17,6	25	70,4/70,7	2867
400-0056 (4.0056)	40	53	77,7	48	36,5	23	3	24	4	58,4	100	23,2	35,8	78,1/78,5	2810
400-0058 (4.0058)	45	59	88,4	57	44	30	3,5	26	3	83,8	132,3	27,7	42	88,9	2811
400-0061 (4.0061)	60	71	107,7	69	55	31	4	35	5	94,2	160,7	38,6	65,2	108,2/108,5	2862
400-0062 (4.0062)	60	80	123	72,3	56	37	5	40	5	128	226,8	53	92	Upon request	2891
400-0063 (4.0063)	60	108	149	78,5	58,5	45	5,5	50	3	172,3	325,9	133,3	244	Upon request	2757
400-0011 (4.0011)	60	108	149	86	67	45	5,5	50	3	172,3	325,9	133,3	244	Upon request	2757
400-0037 (4.0037)	80	120	174	95	71	55	7	63	7	265	488	205,3	381	Upon request	Upon request
400-0039 (4.0039)	80	120	185	95	71	55	7	63	7	265	488	205,3	381	Upon request	Upon request

C = dynamic carrier number
Co = static carrier number
Ca = axial dynamic load number

Coa = axial static load rating
Weldable shaft journal made of steel St52 - tolerance -0.05mm