



Technical data -I-profiles hot rolled structural steel

Type	(b)	b1	Tol.	b2	Tol.	h	Tol.	h1	Tol.	c	d	r1	r2	Wt. in kg per meter	Wx cm ³
3018	98	14	±0,5	70	+1	65	±1	9	±0,5	15	3	91° +1°	10°	19,4	70
3019	113,9	18	±0,5	77,9	+1	66	±1	11	±0,5	15	3	91° +1°	10°	25,3	102
3275	129,6	20,5	±0,5	88,6	+1	72	±1,25	12	±0,5	15	3	91° +1°	10°	31,2	143
3020	129,6	20,5	±0,5	88,6	+1	81	±1,25	12	±0,5	15	3	91° +1°	10°	34,1	160
2912	140,2	18,96	±0,8	102,28	-0,81	69,9	±1,60	12,7	±0,5	-	-	-	-	31,2	157
3100	152,4	22	±0,5	108,4	±0,5	83	±1	14	±0,5	20	3	91° +1°	12°	40,8	219
3353	175	25,6	±0,5	123,8	±0,5	90	±1,30	15	±0,5	20	5	91° +1°	5°	51,4	322

- Profiles can be supplied in any desired length up to a maximum of 12 meters

- Do not paint, coat, etc. on the inside profiles